

**Air Flux 5300 A**

AF5300A 79-3

8733500299

To the extent applicable to the product, the following data are based on the requirements of Regulation (EU) 2016/2281.

Productdata	Symbol	Unit	8733500299
<b>Information for air-to-air air conditioners (usage of this product for cooling purposes, table 11)</b>			
Outdoor side heat exchanger of air conditioner		air	
Indoor side heat exchanger of air conditioner		air	
Type		vapour compression	
Driver of compressor		electric motor	
Rated cooling capacity	$P_{rated,c}$	kW	78,5
Design load $P_{designc}$	$P_{designc}$	kW	78,5
Seasonal space cooling energy efficiency	$\eta_{s,c}$	%	245,0
Seasonal energy efficiency ratio	SEER		6,2
<b>Declared cooling capacity for part load at given outdoor temperatures <math>T_j</math> and indoor 27°/19°C (dry/wet bulb)</b>			
Declared capacity for cooling at indoor 27(19) °C and outdoor 35 °C	$P_{dc}$	kW	78,5
Declared capacity for cooling at indoor 27(19) °C and outdoor 30 °C	$P_{dc}$	kW	52,4
Declared capacity for cooling at indoor 27(19) °C and outdoor 25 °C	$P_{dc}$	kW	33,8
Declared capacity for cooling at indoor 27(19) °C and outdoor 20 °C	$P_{dc}$	kW	15,4
Degradation co-efficient cooling	$C_{dc}$		0,3
<b>Declared energy efficiency ratio or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor Temperatures <math>T_j</math></b>			
Declared energy efficiency ratio at indoor 27(19) °C and outdoor 35 °C	EERd		3,2
Declared energy efficiency ratio at indoor 27(19) °C and outdoor 30 °C	EERd		4,3
Declared energy efficiency ratio at indoor 27(19) °C and outdoor 25 °C	EERd		6,7
Declared energy efficiency ratio at indoor 27(19) °C and outdoor 20 °C	EERd		14,5
<b>Power consumption in modes other than active mode</b>			
Off mode	$P_{OFF}$	kW	0,085
Thermostat-off mode	$P_{TO}$	kW	0,000
Crankcase heater mode	$P_{CK}$	kW	0,085
In standby mode	$P_{SB}$	kW	0,085
<b>Other items</b>			
Capacity control			variable
Sound power level, outdoor	$L_{WA}$	dB	90,0
Sound power level, indoor	$L_{WA}$	dB	-
Air flow rate, outdoor measured	$m^3/h$	$m^3/h$	25000
Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 2088 kgCO <sub>2</sub> eq. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 2088 times higher than 1 kg of CO <sub>2</sub> , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.			

**Air Flux 5300 A**

AF5300A 79-3

8733500299

To the extent applicable to the product, the following data are based on the requirements of Regulation (EU) 2016/2281.

Productdata	Symbol	Unit	8733500299
<b>Information for heat pumps (usage of this product for heating purposes, table 14)</b>			
Outdoor side heat exchanger of air conditioner		air	
Indoor side heat exchanger of air conditioner		air	
Equipped with a supplementary heater?		No	
Driver of compressor		electric motor	
Rated heating capacity	$P_{rated,h}$	kW	78,5
Design load average climate	$P_{designh}$	kW	43,3
Seasonal space heating energy efficiency	$\eta_{s,h}$	%	145,0
SCOP/A average climate	SCOP/A		3,7
<b>Declared heating capacity for part load at indoor temperature 20°C and outdoor temperature Tj</b>			
Declared capacity for heating (average season) at indoor 20 °C outdoor -7 °C	$P_{dh}$	kW	40,6
Declared capacity for heating (average season) at indoor 20 °C outdoor 2 °C	$P_{dh}$	kW	25,2
Declared capacity for heating (average season) at indoor 20 °C outdoor 7 °C	$P_{dh}$	kW	16,2
Declared capacity for heating (average season) at indoor 20 °C outdoor 12 °C	$P_{dh}$	kW	10,2
Declared capacity for heating (average season) at indoor 20 °C outdoor bivalent temperature	$P_{dh}$	kW	43,3
Declared capacity for heating (average season) at indoor 20 °C outdoor operating limit	$P_{dh}$	kW	43,3
Bivalent temperature heating - average	$T_{biv}$	°C	-10
Operational limit temperature heating - average	$T_{ol}$	°C	-10
Degradation co-efficient heating	$C_{dh}$		0,3
<b>Declared coefficient of performance for part load at given outdoor temperatures Tj</b>			
Declared coefficient of performance (average season) at indoor 20 °C outdoor -7 °C	$COP_d$		2,4
Declared coefficient of performance (average season) at indoor 20 °C outdoor 2 °C	$COP_d$		3,3
Declared coefficient of performance (average season) at indoor 20 °C outdoor 7 °C	$COP_d$		5,8
Declared coefficient of performance (average season) at indoor 20 °C outdoor 12 °C	$COP_d$		6,7
Declared coefficient of performance (average season) at indoor 20 °C outdoor bivalent temperature	$COP_d$		2,0
Declared coefficient of performance (average season) at indoor 20 °C outdoor operating limit	$COP_d$		2,0
<b>Power consumption in modes other than active mode</b>			
In off mode	$P_{OFF}$	kW	0,085
In thermostat-off mode	$P_{TO}$	kW	0,085
In crankcase heater mode	$P_{CK}$	kW	0,145
In standby mode	$P_{SB}$	kW	0,085
<b>Supplementary heater</b>			
Back up heating capacity at reference design conditions		kW	0,0
Type of energy input			-
<b>Other items</b>			
Capacity control			variable
Sound power level, outdoor	$L_{WA}$	dB	90,0
Sound power level, indoor	$L_{WA}$	dB	-
Emissions of nitrogen oxides (only gas- or oil fired)	$NO_x$	mg/kWh	-
Air flow rate, outdoor measured	$m^3/h$	$m^3/h$	25000

**Air Flux 5300 A**

AF5300A 79-3

8733500299

Productdata	Symbol	Unit	8733500299
<p>Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 2088 kgCO<sub>2</sub>eq. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 2088 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.</p>			