

**BOSCH**

Invented for life



Combined Heat and Power

CHP CE 140 NA

Technical Data

	Unit	Performance data
		Outlet / Inlet 90 °C / 70 °C
CHP Outputs		
Electrical output at $\cos(\phi)=1$	kWel	140
Thermal output effective	kWth ($\pm 7\%$)	212
Gas consumption DIN ISO 3046-1	kW ($\pm 5\%$)	384
Modulation Range	%	50% - 100%
Efficiency at mains parallel operation		
Electrical efficiency effective	%	36,5%
Thermal efficiency effective	%	55,2%
Overall efficiency effective	%	91,7%
Power to heat ratio (AGFW FW308)	kWel / kWth	66,0%
Noise		
Primary Silencer	dB(A) in 1m	71,6
Secondary Silencer	dB(A) in 1m	57,2
Engine		
Engine manufacturer	-	MAN
Model	-	E2876 E312
Cylinder arrangement	-	Reihe
Number of cylinders	-	6
Dimension and Weight		
Length CHP	mm	3730
Width CHP	mm	1160
Height CHP	mm	1930
Operating weight max. features ca	kg	4000

Due to our ongoing commitment to product improvement these datasheets are subject to change without notice.

Please note: All noise measurements are stated as Sound Pressure Levels (SPL) at 1m. Detailed noise report available on request.

All rights reserved
Copyright © 7/2018

Bosch KWK Systeme GmbH
Justus-Kilian-Straße 29-33
35457 Lollar

Our BIM files can be downloaded from: <https://www.bosch-industrial.com/cad-bim-data>